

	PVC	PURA [®] BACONS
Pile Material	100 % Polyamide	100 % Polyamide
Pile Insert Weight ISO 8543	±600 g/m ²	±600 g/m ²
Use Class EN 1307	33	33
Fire Behavior Euroclass EN 13501	Cfl / s1	Cfl / s1
Dimensions Rolls	100/200 cm ±20 m ¹	100/200 cm ±20 m ¹
Dimensions Mats	60/90, 90/150 cm	60/90, 90/150 cm
Backing	PVC	PU
Sand Absorption Class	2	2
Optical Class	NPD	NPD
Water Absorption Capacity TNO W6034	±3,8 l/m ²	±3,8 l/m ²
Total Weight ISO 8543	±3.000 g/m ²	±2.700 g/m ²
Pile Height ISO 1766	±6,5 mm	±6,5 mm
Total Height ISO 1765	±8,0 mm	±8,0 mm
Pile Density ISO 8543	0,079 g/cm ²	0,079 g/cm ²
Number of Tufts ISO 1763	±64.500 /m ²	±64.500 /m ²
Durability EN 1963	33	33
Comfort EN 1307	LC1	LC1
Dimensional Stability ISO 2551	< 0,4 %	< 0,4 %
Light Fastness ISO 105 B02	> 7	> 7
Water Fastness ISO 105 B01	4 - 5	4 - 5
Rubbing Fastness ISO 105 X12	4 - 5	4 - 5
Salt Water ISO 105 E02	4 - 5	4 - 5
Shampoo BS 1006	4 - 5	4 - 5
Organic Solvents ISO 105 X05	4 - 5	4 - 5
Electronic Charge ISO 6356	< 0,1 kV	< 0,1 kV
Slip Resistance EN 13893	DS	DS
Yarn Construction	Bouclé	Bouclé
Pattern	Mottled	Mottled
Colors	3	3
Suitability for Stairs EN 1963	Intensive use	Intensive use
Suitability for Chairs with Castors EN 985	Intensive use	Intensive use
Primary Backing	PET/PA Non-woven Fabric	PET/PA Non-woven Fabric
Declaration of Performance	Available	Available

Information: For custom-sized carpets, such as cover-style carpets, piped carpets, serged carpets, or stair mats, there may be deviations in height or weight. The technical specifications refer to the wall-to-wall carpet variant.