

Konstruktion Construction Description:	1/10" Getuftete Schlinge, meliert 1/10" Tufted loop pile, intermingled 1/10" Bouclé tufté, mélangé
Zusatzeigenschaften/ Additional properties/ Autres propriétés:	
Polnutschicht Pile material Composition de la fibre:	100% PA 6
Grundmaterial Carrier material Composition du support:	100% PP
Rücken Backing Dossier:	Ecoback grau oder texback® smart Ecoback grey or texback® smart Ecoback gris ou texback® smart
Gesamtgewicht Total weight Poids total:	ca. 1250 g/m ²
Poleinsatzgewicht Pile weight Poids de velours:	ca. 420 g/m ²
Polnutschichtgewicht Weight of pile material Poids du velours utile:	ca. 265 g/m ²
Poldicke Pile thickness Epaisseur du velours:	ca. 3.30 mm
Gesamtdicke Total thickness Epaisseur totale:	ca. 6.30 mm
Noppenzahl Number of tufts Nombre de points:	ca. 2212/dm ²
Trittschallschutz Impact noise insulation Isolation acoustique:	DIN EN ISO 10140 ΔLw = ≥ 10 dB
Schallabsorptionsgrad Sound absorption Absorption phonique:	DIN EN ISO 354 Hz: 125 250 500 1000 2000 4000 αw: -- αs:
Wärmedurchlasswiderstand Thermal resis. Résist. Thermique:	DIN ISO 8302:1991 1/λ = ≤ 0,15 m ² K/W
Brandverhalten Fire rating Comportement au feu:	DIN EN 13501-1
Brandklasse Fire class Classement feu:	Cfl-s1 unverklebt oder verklebt / unglued or glued / non-collé ou collé
max. Aufladung max. static resistance Charge électrique max.:	DIN EN 1815 Bl.2 ≤ 2,0 KV
Durchgangswiderstand Vertical resistance Résistance transversale :	DIN ISO/ DIS 10965Bl.1R _{DT} ≤ 10 ¹⁰ Ω
Oberflächenwiderstand Surface resistance Résistance surfacique :	DIN ISO/ DIS 10965Bl.1R _{OT} ≤ 10 ¹⁰ Ω
Wasserechtheit Water fastness Comportement à l'eau:	DIN EN ISO 105-E01 mind. Note/ N / min.note 4
Farbveränderung Colour-changes Modification de la couleur:	DIN EN ISO 105-E01 mind. Note/ N / min.note 4
Lichtechtheit Light fastness Comportement à la lumière:	DIN EN ISO 105-B02 mind. Note/ N / min.note 5
Reibechtheit Rubbing fastness Comportement au frottement:	DIN EN ISO 105-X12 mind. Note/ N / min.note 4



13
Hameln Teppichwerke
GmbH & Co. KG
Kuhlmannstraße 11
D - 31785 Hameln

22

Tuftingartikel PA mit Textilrücken (unverklebt)

EN 1307
DOP: 1062#2+6/509+508



DL NA
PCP HCHO

EN 14041:2004/AC:2006
NB: 1658 AB: 0321
Textile floor covering to be
used within a building

Alle Artikel der Hameln Teppichwerke, die mit dem SCS INDOOR ADVANTAGE GOLD Zertifikat ausgezeichnet sind, entsprechen den LEED Kriterien des US Green Building Council.

Each product from Hameln Teppichwerke who received the SCS INDOOR ADVANTAGE GOLD certificate comply with the LEED criteria from the US Green Building Council.

Tous les produits de Hameln Teppichwerke qui sont marqués du certificat SCS INDOOR ADVANTAGE GOLD répondent aux critères LEED d' US Green Building Council.



Information: For custom-sized carpets, such as cover-style carpets, piped carpets, serged carpets, or stair mats, there may be deviations in height or weight. The technical specifications refer to the wall-to-wall carpet variant.